

Wall Top Checklist

CHECK	MATERIALS NEEDED	COMMENTS
	Brackets	Placed every 3m, Change in direction, either side of the Gate and on the Gate
	Nail-In Anchors	2 per Bracket
	Stays, Lugs and Accessories to attach to Stays	Every 50m, Change in direction and on the Gate
	Stay Sleeves	1 per Stay
	Tensioners	1 per line of fence every 50m, Change in direction and on Gate
	Comp Springs	1 per line of fence every 50m, Change in direction and on Gate
	Large Tail Spring Hook	1 per Tensioner and 1 per Comp Spring
	Wire	Use the length of the fence multiplied by the amount of lines, eg 100 x 20 lines
	Line Clamps	If required, for Joints and Loops
	Ferrules	If required, double the amount of Tensioners and Comp Springs
	HT Cable	30m, 100m or 200m rolls available
	Earth Spikes	Placed every 30m of fence line plus 3 for the energizer
	Warning Signs	Placed every 10m of the fence line, gates and change of direction
	Gate Contact	1 per gate to carry over power
	Universal Gate Contact Bracket	If required, 1 per gate Contact
	Accessories for Gate	SQ Tube Wall Top Brackets, Stay and Lug, Stay Lug, Tensioner, Large Tail Hooks, Comp Spring
	Energizer	Model, 1 Zone or 2 Zone
	Keypad	To match energizer
	Lightning Diverter	2 per zone (single) or 1 Dual Pole per zone
	Siren	Maximum 30w Siren
	Enclosure (Outside)	Steel or Fibreglass
	Strobe Light	1 per zone
	Comms Cable	100m rolls only
	Fence Light	Maximum of 3 per fence
	Conduit Accessories	If required
	Concrete	If required
	Loops	If required
	Tools	If required

