CHECK	MATERIALS NEEDED FOR <u>FREE STANDING</u> FENCE	COMMENTS
	CORNER POLES	Placed every 50m or 100m, Change in direction and either side of the Gates
	CORNER STAYS	2 per corner pole, except at the start and end and either side of the gate
	M10 NUT & BOLT FOR THE ROUND STAY	1 per stay
	Y STANDARDS	Placed every 3m
	CLIP ON INSULATORS	20 per 2.4 m y standard or 24 per 3m ystandard
	TENSIONERS	20 per 2.4m corner pole and 24 per 3m corner pole
5.4777	STRAINERS	20 per 2.4m corner pole and 24 per 3m corner pole
	WIRE	Use the lentgh of the fence multiply by the amount of lines, eg 100 x 20 lines
	S-HOOKS	40 per 2.4m corner pole and 48 per 3m corner pole
	LINE CLAMPS	If required, for joints and loops
	FERRULES	If required, double the amount of tensioners and strainers
	HT CABLE	30m, 100m or 200m rolls avaliable
	EARTH SPIKES	Placed every 30m of fence line plus 3 for the energizer
	WARNING SIGNS	Placed every 10m of fence line, gates and change of direction
	GATE CONTACT & BRACKET	1 per gate to carry over power
	ACCESSORIES FOR GATE	Bbrackets, tensioner, hooks strainer ect
	ENERGIZER	Model, 1 zone or 2 zone ect
	KEYPAD	To match energizer
	SIREN	Max 30w siren
	ENCLOSURE (OUTSIDE)	Steel or Fibre glass
	STROBE & MOUNTING BRACKET	1 per zone
	COMMS CABLE	100m rolls only
	FENCE LIGHT	Max 3 per fence
	CONDUIT ACCESSORIES	If required
7	CONCRETE	If required
	LOOPS	If required
	TOOLS	If required
	LIGHNING DIVERTERS	2 per zone